



# DUAL DISPLAYS MILITARY CONSOLE

## CUSTOM ENGINEERED FOR AEROSPACE & DEFENSE

- ◆ Dual 23.8" TFT-LCD Portable GPU Server
- ◆ Intel® Ice Lake 3rd Gen. Xeon® Scalable CPU
- ◆ NVIDIA® Quadro RTXA4000 GPU (6,144 CUDA)
- ◆ Redundant AC 100~240V Input
- ◆ MIL-STD-461 18V~36V DC-Input (optional)
- ◆ Extreme Temperature: -20°C to +55°C
- ◆ MIL-STD-810 Vibration Method 514.6: ◎Acceleration: 5.0 Grms
- ◆ MIL-STD-810 Vibration Method 514.6: ◎PSD: 0.01257 g<sup>2</sup>/Hz
- ◆ MIL-STD-810 Shock Method 516.6: ◎Wave Form: Half Shine Wave
- ◆ MIL-STD-810 Shock Method 516.6: ◎Acceleration: 20G



intel partner

**7STARLAKE**

© Copyright 7starlake Co, Ltd. All Rights Reserved. 202511

7STARLAKE.com

# MILITARY GRADE PANEL MOUNT DISPLAYS

24"



## Military Grade Smart Display

### ■ SKY24-P04

- ◆ 23.6" TFT LCD 2560 x 1600 4K (16:9)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch
- ◆ MIL-DTL 38999 Connector: DC-in; HDMI/DP(optional); USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 580x420x58mm
- ◆ Sunlight readable Up to 1000 nits

21"



## Military Grade Smart Display

### ■ SKY21-P04

- ◆ 21.5" TFT LCD 1920 x 1028 (16:9)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch
- ◆ MIL-DTL 38999 Connector: DC-in; HDMI/DP(optional); USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 520x357x58mm
- ◆ Sunlight readable Up to 1000 nits

15"



## Military Grade Smart Display

### ■ SKY15-P04

- ◆ 15" TFT LCD 1920 x 1028 (16:9)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch with EMI mesh (Options)
- ◆ MIL-DTL 38999 Connector: DC-in; HDMI/DP(optional); USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 380x275x58mm
- ◆ Sunlight readable Up to 1000 nits

12"



## Military Grade Smart Display

### ■ SKY12-P04

- ◆ 12.1" TFT LCD 1024 x 768 (4:3)
- ◆ Intelligent Heater (Options)
- ◆ IP65/ MIL-STD-810 Standards
- ◆ Glass-Film-Glass (GFG) Resistive Touch with EMI mesh (Options)
- ◆ MIL-DTL 38999 connector: DC-in; HDMI/DP(optional); USB
- ◆ MIL-STD-461/EMI Filter (Options)
- ◆ Dimension: 308x263x66.3mm
- ◆ Sunlight readable Up to 1000 nits